



FEATURES

Bearings: Precision Ball or Straight Roller

Temperature: Maximum to 230° F

Hardness: 45-65 Durometer D scale

Envirothane wheels feature a solid, non-marking polyurethane used for high load capacities. This top quality wheel will not damage floors and will not develop flat spots under standing loads. Tested for medium load capacities, the Envirothane wheel is harder than soft rubber. Envirothane wheels resist most chemicals, offer good floor protection and are completely washable. The one piece solid Envirothane makes it virtually maintenance free.



APPLICATIONS

Envirothane wheels are excellent for tow line applications, platform trucks, large stock trucks, textile carts, food service equipment and other abusive applications.

WHEEL		CAPACITY			PART NUMBER				
Dia.	Width	Capacity	Hub Length	Bore	Roller Bearing	Ball	Less Bearing	Wt.	
4	2.00	650	2 3/16	1 3/16			04200-62-19	1.5	
4	2.00	650	2 7/16	3/4	04201-62-12			1.5	
4	2.00	650	2 7/16	1/2		04204-62-08		1.5	
4	2.00	650	2 7/16	1/2		04202-62-08*		1.5	
5	2.00	800	2 3/16	1 3/16			05200-62-19	2.0	
5	2.00	800	2 7/16	3/4	05201-62-12			2.0	
5	2.00	800	2 7/16	1/2		05204-62-08		2.0	
5	2.00	800	2 7/16	1/2		05202-62-08*		2.0	
6	2.00	950	2 3/16	1 3/16			06200-62-19	2.5	
6	2.00	950	2 7/16	3/4	06201-62-12			2.5	
6	2.00	950	2 7/16	1/2		06204-62-08		2.5	
6	2.00	950	2 7/16	1/2		06202-62-08*		2.5	
6	2.50	1,200	2 3/4	1 15/16			06255-62-31	7.5	
6	2.50	1,200	2 3/4	1	06255-62-16			7.5	
6	2.50	1,200	2 3/4	1 1/4	06255-62-20			7.5	
6	2.50	1,200	3	3/4		06256-62-12		7.5	
8	2.00	1,100	2 3/16	1			08200-62-19	3.7	
8	2.00	1,100	2 3/16	3/4	08201-62-12			3.7	
8	2.00	1,100	2 7/16	1/2		08204-62-08		3.7	
8	2.00	1,100	2 7/16	1		08202-62-08*		3.7	
8	2.50	1,600	2 3/4	1 15/16			08255-62-31	8.5	
8	2.50	1,600	2 3/4	1	08255-62-16			8.5	
8	2.50	1,600	2 3/4	1	08255-62-20			8.5	
8	2.50	1,600	3	1		08256-62-12		8.5	

*Constructed with precision ball bearings
All dimensions are in inches. All weights are in pounds.