



**FEATURES**

A wide variety of keyway drive wheels are available. Keyway drive wheels are used in various power transmission applications. The keyways are cut to fit a keywayed shaft and are held in place with two set screws. One set screw is placed over the key and one at 90 degrees to the keyway. The most popular models in rubber and soft polyurethane are shown in the charts. Keyway wheels are manufactured in other materials, forged steel or cast iron, are available. Check the wheel widths on the chart and select the appropriate bushing. Costing for specific requirements is also readily available.



Bushing	ID	OD	Length	Key	Wheel Width
KWAA	0.50	1.19	2.44	0.125	2"
KWBB	0.75	1.19	2.44	0.188	2"
KWA	0.50	1.94	3.25	0.125	2-1/2" or 3"
KWB	0.75	1.94	3.25	0.188	2-1/2" or 3"
KWC	1.00	1.94	3.25	0.250	2-1/2" or 3"
KWD	1.25	1.94	3.25	0.250	2-1/2" or 3"
KWE	1.50	2.44	4.25	0.375	4"
KWEE	1.50	2.44	5.25	0.375	5"

WHEEL					PART NUMBER	CAPACITY
Dia.	Width	Hub Length	Bore	Keyway Size		
<b>Drive Rollers--Mold on Rubber Roller Surfaces-Durometer hardness is 70-75A</b>						
3	2	offset	1/2	1/8 x 1/16	03200-70-08-KWAA	300
3	2	offset	3/4	3/16 x 3/32	03200-70-12-KWBB	300
4	2	offset	1/2	1/8 x 1/16	04200-70-08-KWAA	350
4	2	offset	3/4	3/16 x 3/32	04200-70-12-KWBB	350
5	2	2 3/16	1/2	1/8 x 1/16	05200-70-08-KWAA	400
5	2	2 3/16	3/4	3/16 x 3/32	05200-70-12-KWBB	400
6	2	2 3/16	1/2	1/8 x 1/16	06200-70-08-KWAA	425
6	2	2 3/16	3/4	3/16 x 3/32	06200-70-12-KWBB	425
6	3	3 1/4	1/2	1/8 x 1/16	06300-70-08-KWA	500
6	3	3 1/4	3/4	3/16 x 3/32	06300-70-12-KWB	500
6	3	3 1/4	1	1/4 x 1/8	06300-70-16-KWC	500
6	3	3 1/4	1 1/4	1/4 x 1/8	06300-70-20-KWD	500
8	2	2 3/16	1/2	1/8 x 1/16	08200-70-08-KWA	500
8	2	2 3/16	3/4	3/16 x 3/32	08200-70-12-KWB	500
8	3	3 1/4	1/2	1/8 x 1/16	08300-70-08-KWA	850
8	3	3 1/4	3/4	3/16 x 3/32	08300-70-12-KWB	850
8	3	3 1/4	1	1/4 x 1/8	08300-70-16-KWC	850
8	3	3 1/4	1 1/4	1/4 x 1/8	08300-70-20-KWD	850
10	3	3 1/4	1/2	1/8 x 1/16	10300-70-08-KWA	800
10	3	3 1/4	3/4	3/16 x 3/32	10300-70-12-KWB	800
10	3	3 1/4	1	1/4 x 1/8	10300-70-16-KWC	1000
10	3	3 1/4	1 1/4	1/4 x 1/8	10300-70-20-KWD	1000
<b>Drive Rollers--Soft Polyurethane Roller Surfaces-Durometer hardness is 85A</b>						
3	2	3-1/4 offset	1/2	1/8 x 1/16	03200-61-08-KWAA	300
3	2	3-1/4 offset	3/4	3/16 x 3/32	03200-61-12-KWBB	300
4	2	3-1/4 offset	1/2	1/8 x 1/16	04200-66-08-KWAA	350
4	2	3-1/4 offset	3/4	3/16 x 3/32	04200-66-12-KWBB	350
5	2	2 3/16	1/2	1/8 x 1/16	05200-61-08-KWAA	400
5	2	2 3/16	3/4	3/16 x 3/32	05200-61-12-KWBB	400
6	2	2 3/16	1/2	1/8 x 1/16	06200-61-08-KWAA	425
6	2	2 3/16	3/4	3/16 x 3/32	06200-61-12-KWBB	425
6	3	3 1/4	1/2	1/8 x 1/16	06300-66-08-KWA	800
6	3	3 1/4	3/4	3/16 x 3/32	06300-66-12-KWB	800
6	3	3 1/4	1	1/4 x 1/8	06300-66-16-KWC	1600
6	3	3 1/4	1 1/4	1/4 x 1/8	06300-66-20-KWD	1600
8	2	2 3/16	1/2	1/8 x 1/16	08200-61-08-KWA	500
8	2	2 3/16	3/4	3/16 x 3/32	08200-61-12-KWB	500
8	3	3 1/4	1/2	1/8 x 1/16	08300-66-08-KWA	800
8	3	3 1/4	3/4	3/16 x 3/32	08300-66-12-KWB	800
8	3	3 1/4	1	1/4 x 1/8	08300-66-16-KWC	1600
8	3	3 1/4	1 1/4	1/4 x 1/8	08300-66-20-KWD	1600
10	3	3 1/4	3/4	3/16 x 3/32	10300-66-12-KWB	800
10	3	3 1/4	1	1/4 x 1/8	10300-66-16-KWC	1600
10	3	3 1/4	1 1/4	1/4 x 1/8	10300-66-20-KWD	1600
10	4	4 1/4	1 1/2	3/8 x 3/16	10400-66-24-KWE	2500
10	5	5 1/4	1 1/2	3/8 x 3/16	10500-65-24-KWEE*	2500
12	4	4 1/4	1 1/2	3/8 x 3/16	12400-66-24-KWE	3000
12	5	5 1/4	1 1/2	3/8 x 3/16	12500-65-24-KWEE*	3000