



FEATURES

**Bearings:** Precision ball or straight roller

**Temperature:** Maximum to 230° F.

**Hardness:** 75 Durometer A Scale

Softech wheels feature a soft, non-marking tread on a rust-free polyolefin core. Softech wheels reject floor debris, are highly resistant to most chemicals, grease, solvents and acids, and are stain resistant and zero water absorbing. Quiet, easy rolling and shock absorbing, these wheels are excellent for most floor surfaces.



APPLICATIONS

Softech wheels are excellent for platform trucks, food service equipment, textile carts, hotel equipment and other abusive applications.

WHEEL			CAPACITY	PART NUMBER				
Dia.	Width	Hub Length	Bore	Roller Bearing	Ball Bearing	Less Bearing	Wt.	
4	2	250	2 3/16	1 3/16		04200-72-19	1.00	
4	2	250	2 7/16	3/4	04201-72-12		1.00	
4	2	250	2 7/16	1/2		04204-72-08	1.00	
4	2	250	2 7/16	1/2		04202-72-08*	1.00	
5	2	275	2 3/16	1 3/16		05200-72-19	1.50	
5	2	275	2 7/16	3/4	05201-72-12		1.50	
5	2	275	2 7/16	1/2		05204-72-08	1.50	
5	2	275	2 7/16	1/2		05202-72-08*	1.50	
6	2	450	2 3/16	1 3/16		06200-72-19	2.00	
6	2	450	2 7/16	3/4	06201-72-12		2.00	
6	2	450	2 7/16	1/2		06204-72-08	2.00	
6	2	450	2 7/16	1/2		06202-72-08*	2.00	
8	2	600	2 3/16	1 3/16		08200-72-19	2.25	
8	2	600	2 7/16	3/4	08201-72-12		2.25	
8	2	600	2 7/16	1/2		08204-72-08	2.25	
8	2	600	2 7/16	1/2		08202-72-08*	2.25	

\* Constructed with precision ball bearings. All dimensions are in inches. All weights are in pounds.