



FEATURES

NyTec-MD is a nylon filled material which provides a high load capacity, floor protective wheel. The wheel capacities approach those of similar cast iron and steel wheels. Nytec- MD material is resistant to most harsh environments. The non-abrasive and vibration dampening material actually provides a quieter operation when compared to steel or cast iron wheels. When used in wet environments, plain bore NyTec-MD wheels can be used as the material is self lubricating. NyTec wheels are offered with precision tapered, precision ball, and straight roller bearings. For special applications, contact the factory.

WHEEL				PART NUMBER			CAPACITY
Dia.	Width	Hub Length	Bore	Roller	Ball Bearing	Tapered	Capacity
3	2	2 7/16	1/2	03201-39-12	03202-39-08	03209-39-08	780
3	3	3 1/2	1	03301-39-16*		03309-39-16	1170
3	3	3 1/4	1 1/4	03301-39-20			1170
3	4	4 1/2	3/4		03402-39-12	03409-39-12	1560
3	4	4 1/2	1	03401-39-16*		03409-39-16	1560
3	4	4 1/4	1 1/4	03401-39-20*			1560
4	2	2 7/16	1/2	04201-39-12	04202-39-08	04209-39-08	1040
4	3	3 1/2	3/4		04302-39-12	04309-39-12	1560
4	3	3 1/2	1	04301-39-16*		04309-39-16	1560
4	3	3 1/2	1 1/4	04301-39-20*		04309-39-20	1560
4	4	4 1/2	3/4		04402-39-12	04409-39-12	2080
4	4	4 1/2	1		04402-39-16	04409-39-16	2080
4	4	4 1/2	1 1/4	04401-39-20*	04402-39-20	04409-39-20	2080
4	4	4 1/4	1 1/2	04401-39-24			2080
6	2	2 7/16	1/2	06201-39-12	06202-39-08	06209-39-08	1560
6	3	3 1/2	3/4		06302-39-12	06309-39-12	2340
6	3	3 1/2	1	06301-39-16*		06309-39-16	2340
6	3	3 1/2	1 1/4	06301-39-20*		06309-39-20	2340
6	4	3 1/2	1		06402-39-16	06409-39-16	3120
6	4	3 1/2	1 1/4	06401-39-20*	06402-39-20	06409-39-20	3120
6	4	3 1/4	1 1/2	06401-39-24			3120
6	5	5 1/2	1		06502-39-16	06509-39-16	3900
6	5	5 1/2	1 1/4	06501-39-20*	06502-39-20	06509-39-20	3120
6	5	5 1/4	1 1/2	06501-39-24			3120
8	2	2 7/16	1/2	08201-39-12	08202-39-08	08209-39-08	2080
8	3	3 1/2	3/4		08302-39-12	08309-39-12	3120
8	3	3 1/2	1	08301-39-16*	08302-39-16	08309-39-16	3120
8	3	3 1/2	1 1/4	08301-39-20*	08302-39-20	08309-39-20	3120
8	4	3 1/2	1		08402-39-16	08409-39-16	3120
8	4	3 1/2	1 1/4	08401-39-20*	08402-39-20	08409-39-20	3120
8	4	3 1/4	1 1/2	08401-39-24			4160
8	5	5 1/2	1		08502-39-16	08509-39-16	4160
8	5	5 1/2	1 1/4	08501-39-20*	08502-39-20	08509-39-20	4160
8	5	5 1/4	1 1/2	08501-39-24			4160
10	3	3 1/2	3/4		10302-39-12	10309-39-12	3900
10	3	3 1/2	1	10301-39-16*	10302-39-16	10309-39-16	3900
10	3	3 1/2	1 1/4	10301-39-20*	10302-39-20	10309-39-20	3900
10	4	3 1/2	1		10402-39-16	10409-39-16	5200
10	4	3 1/2	1 1/4	10401-39-20*	10402-39-20	10409-39-20	5200
10	4	3 1/4	1 1/2	10401-39-24			5200
10	5	5 1/2	1		10502-39-16	10509-39-16	6500
10	5	5 1/2	1 1/4	10501-39-20*	10502-39-20	10509-39-20	6500
10	5	5 1/4	1 1/2	10501-39-24			6500
12	3	3 1/2	3/4		12302-39-12	12309-39-12	4680
12	3	3 1/2	1	12301-39-16*	12302-39-16	12309-39-16	4680
12	3	3 1/2	1 1/4	12301-39-20*	12302-39-20	12309-39-20	4680
12	4	3 1/2	1		12402-39-16	12409-39-16	6240
12	4	3 1/2	1 1/4	12401-39-20*	12402-39-20	12409-39-20	6240
12	4	3 1/4	1 1/2	12401-39-24			6240
12	5	5 1/2	1		12502-39-16	12509-39-16	7800
12	5	5 1/2	1 1/4	12501-39-20*	12502-39-20	12509-39-20	7800
12	5	5 1/4	1 1/2	12501-39-24			7800
12	6	6 1/2	1		12602-39-16	12509-39-16	9360
12	6	6 1/2	1 1/4		12602-39-20	12609-39-20	9360

CASTER CONCEPTS WILL MODIFY ANY CASTER TO MEET CUSTOMER SPECIFICATIONS

Caster Concepts, Inc., 16000 E. Michigan Ave., Albion, MI 49224 (517) 629-8838 Facsimile (800) 800-0036 www.casterconcepts.com