






| ITEM NO. | QTY. | PART/DRAWING NO. | DESCRIPTION | MATERIAL |
|----------|------|---------------------|--|-----------|
| 1 | 1 | 37-08200-00-1HDLPTG | 37 SER. 8.00 X 2.00 SWL. RIG C/W HDSL,PLB & TG | MISC. |
| 2 | 1 | 08202-44-12 | Ø8.00 X 2.00 ET85 TWERGO WHEEL C/W .75 BORE | MISC. |
| 3 | 1 | AX085400 | 1/2-20 X 3-3/8 SOLID AXLE ZINC | AISI 1038 |
| 4 | 1 | LN08200 | 1/2-20 TOP LOCK NUT | AISI 1038 |

- NOTES:
1. CASTER IS RATED AS 750 LBS @ WALKING SPEEDS, INTERMITTENT USE.
 2. AT 750 LBS OF THE LOAD THERE WILL BE A CALCULATED FLOOR LOAD OF 404 PSI.
 3. ESTIMATED COF OF ROLLING RESISTANCE IS 3% OF LOAD TO START MOVING AND 1% OF LOAD TO MAINTAIN. (THIS IS FIGURING 2 SWIVEL AND 2 RIGID CASTERS ON SMOOTH, FLAT CONCRETE) APPLICATION AND FLOOR CONDITIONS WILL IMPACT THIS.
 4. CASTER WEIGHT: 13.71 LBS



| | | | | | | |
|---|------------------|--|---|-----------|------------------------------------|---|
|  CASTER CONCEPTS, INC. 16000 E. MICHIGAN AVE. ALBION, MI 49224 (517) 629-8838 casterconcepts.com | TOLERANCE SPECS. | | UNLESS OTHERWISE SPECIFIED THE FOLLOWING TOLERANCES APPLY: .XX = ±.030 .XXX = ±.010 X° = ±1.0° PART TO BE FREE OF BURRS AND SHARP EDGES | | DESCRIPTION: 37-08202-44-1HDLPTGSP | |
| | FINISH SPECS. | | ZINC PLATING ON RIG | | PART/DRAWING NO: SP18120503HDLPTG | |
| WHERE USED: | | | | | DATE: | 3/29/2019 |
| CHECKED BY: | NEKIBUR R. | | APPROVED BY: | | SCALE: | 1:2 C-SIZE |
| MATERIAL SPECS. | | | | DRAWN BY: | PRAVEEN K. | THIRD ANGLE  |

NOTICE: THIS DRAWING AND DESIGN INFORMATION CONTAINED HEREIN SHALL REMAIN THE SOLE PROPERTY OF CASTER CONCEPTS INC. IT IS SUBMITTED FOR USE IN REFERENCE ONLY AND SHALL NOT BE DUPLICATED OR GIVEN TO A THIRD PARTY WITHOUT THE WRITTEN CONSENT OF CASTER CONCEPTS INC. THIS DRAWING MUST BE RETURNED TO CASTER CONCEPTS INC. UPON REQUEST AT ANY TIME. ACCEPTANCE OF THIS DRAWING SHALL BE CONSTRUED AS AN AGREEMENT OF THESE TERMS.