



ITEM NO.	QTY.	PART/DRAWING NO.	DESCRIPTION	MATERIAL
1	1	2-91-18600-00-1LF	2-91 SER. 18.00 X 6.00 PNEU. SWL RIG C/W SL & FCB	MISC.
2	2	23609-76-20	6.50/10 PNEU 1-1/4 TB 10 PLY, 4-1/8 HUB LENGTH	MISC.
3	1	AX2033800	1-1/4-12 X 21-1/8 PNEUMATIC AXLE	ETD 150
4	1	AX084800	1/2-20 X 3 HHCS	AISI 1038
5	1	LN08200	1/2-20 TOP LOCK NUT	AISI 1038
6	2	SB2024701	1.25 X 1.50 X .50 SPACER	AISI 1026
7	2	KY032800	3/16 X 1-3/4 ROLL PIN	STEEL
8	2	SN201216	1-1/4 -12 SLOTTED JAM NUT ZINC PLATED	STEEL

- NOTES:
1. CASTER IS RATED AS 5,550 LBS @ WALKING SPEEDS, INTERMITTENT USE.
 2. ESTIMATED COF OF ROLLING RESISTANCE IS 5% OF LOAD TO START MOVING AND 2% OF LOAD TO MAINTAIN. (THIS IS FIGURING 2 SWIVEL AND 2 RIGID CASTERS ON SMOOTH, FLAT CONCRETE) APPLICATION AND FLOOR CONDITIONS WILL IMPACT THIS.
 3. CASTER WEIGHT: 318.84LBS



<div><div><div></div></div><div>CASTER CONCEPTS, INC.</div></div> <div>16000 E. MICHIGAN AVE. ALBION, MI 49224 (517)629-8838 casterconcepts.com</div>	TOLERANCE SPECS.		UNLESS OTHERWISE SPECIFIED THE FOLLOWING TOLERANCES APPLY: .XX = ±.030 .XXX = ±.010 X° = ±1.0° PART TO BE FREE OF BURRS AND SHARP EDGES		DESCRIPTION: 2-91-23609-76-1HDLFSP	
	FINISH SPECS.		GOLD POWDER COAT ON RIG		PART/DRAWING NO:	SP18120401HDLF
	WHERE USED:		APPROVED BY:		DATE:	4/1/2019
	CHECKED BY: NEKIBUR R.		MATERIAL SPECS.		DRAWN BY: PRAVEEN K.	
			THIRD ANGLE 			

NOTICE: THIS DRAWING AND DESIGN INFORMATION CONTAINED HEREIN SHALL REMAIN THE SOLE PROPERTY OF CASTER CONCEPTS INC. IT IS SUBMITTED FOR USE IN REFERENCE ONLY AND SHALL NOT BE DUPLICATED OR GIVEN TO A THIRD PARTY WITHOUT THE WRITTEN CONSENT OF CASTER CONCEPTS INC. THIS DRAWING MUST BE RETURNED TO CASTER CONCEPTS INC. UPON REQUEST AT ANY TIME. ACCEPTANCE OF THIS DRAWING SHALL BE CONSTRUED AS AN AGREEMENT OF THESE TERMS.