



CASTER 16000 E. MICHIGAN AVE. ALBION, MI 49224	TOLERANCE SPECS.	UNLESS OTHERWISE SPECIFIED THE FOLLOWING TOLERANCES APPLY: .XX = $\pm .030$ .XXX = $\pm .010$ X° = $\pm 1.0^{\circ}$	DESCRIPTION: 81 SER. 10.00 X 4.00 SWL. CASTER C/W SL & FCB				
CONCEPTS, INC. (517)629-8838 casterconcepts.com		PART TO BE FREE OF BURRS AND SHARP EDGES	PART/DRAWING NO: 81-10409-65-1LF		DATE: 6/8/2023		3
WHERE USED:	FINISH SPECS.	GOLD POWDER COATING ON RIG, GRAY PAINT ON WHEEL CORE			scale:	1:4	C-SIZE
CHECKED BY: PRAVEEN K.	MATERIAL SPECS.	APPROVED BY:	DRAWN BY	FIELD C FINCH	THIRD ANGLE		
NOTICE: THIS DRAWING AND DESIGN INFORMATION CONTAINED HEREIN SHALL REMAIN THE SOLE PROPERTY OF CASTER CONCEPTS INC. IT IS SUBMITTED FOR USE IN REFERENCE ONLY AND SHALL NOT BE DUPLICATED OR GIVEN TO A THIRD PARTY							

NOTICE:THIS DRAWING AND DESIGN INFORMATION CONTAINED HEREIN SHALL REMAIN THE SOLE PROPERTY OF CASTER CONCEPTS INC. IT IS SUBMITTED FOR USE IN REFERENCE ONLY AND SHALL NOT BE DUPLICATED OR GIVEN TO A THIRD PARTY WITHOUT THE WRITTEN CONSENT OF CASTER CONCEPTS INC. THIS DRAWING MUST BE RETURNED TO CASTER CONCEPTS INC. UPON REQUEST AT ANY TIME. ACCEPTANCE OF THIS DRAWING SHALL BE CONSTRUED AS AN AGREEMENT OF THESE TERMS.

DRAWING NO.	DESCRIPTION	MATERIAL
10400-00-1LF	81 SER. 10.00 X 4.00 SWL. RIG C/W SL FCB	MISC.
0409-65-16	Ø10.00 X 4.00 95-A THICK TREAD POLY WHEEL	MISC.
AX169600	1-14 X 6 GRADE 5 HHCS	AISI 1038
LN161413	1"-14 LOW HEIGHT FLEXLOC NUT	STEEL

